

## UCCONNECT

Patchcord 4P Cat8.2 – Cat8.2, 40GbE Ethernet, colour grey/grey

Side A: Cat8.2-plug, 4 pair

Side B: RJ45, 4 pair



### Patch Cord 4-Pair, Category 8.2 – RJ45

- 4 Chamber Design
- Fully compatible with Cat 7 and Cat 7a
- Shielded Design
- 3<sup>rd</sup> Party Approved by GHMT
- 40GbE

## Specification

Item	Description
Cable	4P 4x2xAWG26/7 S/FTP, flex., 100 Ohm Outer jacket: Compound free of halogens
A Side	Cat8.2 plug 4P bend relief yellow
B Side	RJ45 plug 4P bend relief yellow
Colours	Grey RAL7035 or yellow RAL1021

## Technical data

Material Code	Material Description	Description Code	Weight	Items per Packaging Unit
YPCBP02490	Patchcord 4P Cat8.2 - RJ45, 40 GbE Ethernet 8.2 flex, color grey/grey Side A: Cat8.2-plug, 4 pair Side B: RJ45-plug, compilation 1-1 length 0,50 m	UC C2000 PC 4P RJ SF GY L00050 40GbE	34	10
YPCBP02491	Patchcord 4P Cat8.2 - RJ45, 40 GbE Ethernet 8.2 flex, color grey/grey Side A: Cat8.2 Plug, 4 pair Side B: RJ45-plug, compilation 1-1 length 1,00 m	UC C2000 PC 4P RJ SF GY L00100 40GbE	50	10
YPCBP02492	Patchcord 4P Cat8.2 - RJ45, 40 GbE Ethernet 8.2 flex, color grey/grey Side A: Cat8.2 Plug, 4 pair Side B: RJ45-plug, compilation 1-1 length 1,50 m	UC C2000 PC 4P RJ SF GY L00150 40GbE	69	10
YPCBP02493	Patchcord 4P Cat8.2 - RJ45, 40 GbE Ethernet 8.2 flex, color grey/grey Side A: Cat8.2 Plug, 4 pair Side B: RJ45-plug, compilation 1-1 length 2,00 m	UC C2000 PC 4P RJ SF GY L00200 40GbE	72	10
YPCBP02494	Patchcord 4P MMC - RJ45, 40 GbE Ethernet 8.2 flex, color grey/grey Side A: Cat8.2-plug, 4 pair Side B: RJ45-plug, compilation 1-1 length 5,00 m	UC C2000 PC 4P RJ SF GY L00500 40GbE	120	10

© PRYSMIAN GROUP 2016, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.