

Category 6 F/FTP Euroclass C_{ca} Cables

Datasheet: GD103458v2

Brand-Rex | a LEVITON company


APPLICATION

The Brand-Rex C6F/FTP C_{ca} cables are compliant with the European Construction Products Regulation, achieving Euroclass level C_{ca} according to EN 13501-6. These C_{ca} Euroclass cables also have optimum levels of smoke emission, flaming droplets and acid gas production making them a versatile choice for most internal installation. The C6F/FTP C_{ca} Euroclass cables are suited to any high density backbone installation where people safety in the case of fire is a high priority.

The Brand-Rex C6F/FTP cables exceed the Category E performance standards. They are rated to 250MHz and are suitable for use in all Class E structured wiring cable systems. The applications supported include Gigabit Ethernet, PoE and PoE+ and broadband video transmissions at frequencies as high as 250MHz.

FEATURES AND BENEFITS

- 23 AWG Solid Annealed Copper Wire
- 4 Twisted Pairs Individually Screened and cabled together – providing EMI immunity
- Overall Aluminium Polyester Screen – for improved shielding efficiency and increased heat dissipation
- Designed to Support all Class E protocols including Gigabit Ethernet
- Supports Power Over Ethernet (PoE) and Power Over Ethernet Plus (PoE+) Applications
- Enhanced HFFR-LS* material meets the requirements of the Construction Products Regulation (CPR) Euroclass C_{ca}
- Green† Coloured Jacket to identify Euroclassification level C_{ca}
- Included in the Leviton and Brand-Rex 25 Year System Warranties when used in conjunction with Leviton or Brand-Rex copper connectivity. System warranties available for qualified projects installed by certified contractors



* Halogen Free Flame Retardant – Low Smoke

† Also available in a range of non-standard colours

STANDARDS

Applicable Cable Standards: IEC 61156-5 and EN50288-5-1

REACTION TO FIRE

CHARACTERISTIC	STANDARD	RATING
Single Cable Flame Rating	IEC 60332-1-2	Pass
Bundled Cable Flame Rating	EN 50399 20.5kW source	C _{ca}
Smoke Production	EN 50399	s1a
Flaming Droplets / Particles	EN 50399	d1
Acid Gas Emission / Acidity	EN 50267-2-3	a1
Euroclassification	EN 13501-6	C _{ca} s1a d1 a1

Category 6 F/FTP Euroclass C_{ca} Cables

Datasheet: GD103458v2



PRIMARY ELECTRICAL PARAMETERS

CHARACTERISTIC	SPECIFICATION	TYPICAL PERFORMANCE @ 20°C
Conductor Loop Resistance	Max 19 Ω / 100m	14Ω / 100m
Conductor Resistance Unbalance	Max 2%	0.1%
Insulation Resistance	>5GΩ.km	>50GΩ.km
Dielectric Strength	2500 Vdc/2secs	Pass

SECONDARY ELECTRICAL PARAMETERS

CHARACTERISTIC	SPECIFICATION	TYPICAL PERFORMANCE @ 20°C
Velocity of Propagation	<534nsec/100m @ 100MHz	413nsec/100m @ 100MHz
Delay Skew	Max 45nsec/100m @ 100MHz	4nsec/100m @ 100MHz
Mean Characteristic Impedance	100Ω +/- 5Ω @ 100MHz	100Ω ± 3Ω @ 100MHz
Coupling Attenuation	Type 1b	84dB
Transfer Impedance	Grade 2	11mΩ/m @ 10MHz

ELECTRICAL PERFORMANCE

Frequency (MHz)		1	4	10	20	100	200	250	500	550
Insertion Loss (dB/100m)	Standard	2.1	3.8	6.0	8.5	19.9	29.1	33.0	na	na
	<i>Typical</i>	1.9	3.5	5.5	7.8	18.0	26.1	29.4	43.0	45.4
NEXT (dB)	Standard	66.0	65.3	59.3	54.8	44.3	39.8	38.3	na	na
	<i>Typical</i>	100.0	100.0	100.0	100.0	94.3	88.9	87.1	81.7	81.0
PSNEXT (dB)	Standard	64.0	63.3	57.3	52.8	42.3	37.8	36.3	na	na
	<i>Typical</i>	97.0	97.0	97.0	97.0	91.3	85.9	84.1	78.7	78.0
ELFEXT (dB/100m)	Standard	66.0	58.0	50.0	44.0	30.0	24.0	22.0	na	na
	<i>Typical</i>	90.0	90.0	90.0	84.8	70.8	64.8	62.8	56.8	56.0
PSELFEXT (dB/100m)	Standard	64.0	55.0	47.0	41.0	27.0	21.0	19.0	na	na
	<i>Typical</i>	87.0	87.0	87.0	81.8	67.8	61.8	59.8	53.8	53.0
Return loss (dB)	Standard	na	23.0	25.0	25.0	20.1	18.0	17.3	na	na
	<i>Typical</i>	27.0	30.0	30.0	30.0	25.1	23.0	22.3	20.2	19.9
ACR (dB/100m)	<i>Typical</i>	98.1	96.5	94.5	92.2	76.3	62.8	57.7	38.7	35.6
PSACR (dB/100m)	<i>Typical</i>	95.1	93.5	91.5	89.2	73.3	59.8	54.7	35.7	32.6

Category 6 F/FTP Euroclass C_{ca} Cables

Datasheet: GD103458v2

Brand-Rex | a LEVITON[®] company

INSTALLATION

Temperature (Installation)	0°C to +50°C	Min Bend Radius (Installation)	8 x Outer Diameter
Temperature (Operation)	-20°C to +75°C	Min Bend Radius (Operation)	4 x Outer Diameter
Max Tensile Load (Installation)	10kg per simplex cable	Field Test NVP Value	0.80
Segregation Class	Class D		

PRINT LEGEND

Example print legend:

[Length Mark]m BRAND-REX a LEVITON company C6F/FTP-Cca Cat 6 F/FTP EN 50399 Euroclass Cca s1a d1 a1 NVP 0.80 MADE IN UK [ID number] [Week/Year]

STANDARD PACKAGING SPECIFICATIONS

Brand-Rex Part Number	Packaging Length (m)	Colour	Nominal Cable Diameter (mm)	Nominal Cable Weight (kg/km)	Reel Size Flange x Width (mm)	Gross Weight (kg/Item)	Items Per Pallet
C6F/FTP-Cca-500GN	500	Green†	7.5	57.9	465 x 390	31.9	6
C6F/FTP-Cca-1000GN	1000	Green†	7.5	57.9	600 x 405	64.4	4

†Also available in a range of non-standard colours

“Brand-Rex is dedicated to designing, developing and manufacturing sustainable high performance structured cabling and speciality cabling solutions”

The information contained in this document is valid and correct at the time of issue. Brand-Rex reserves the right to modify details without notice in light of subsequent standard/specification changes and ongoing technical developments.