

Category 6 F/FTP Euroclass D_{ca} Cables

Datasheet: GD103610v1

Brand-Rex | a **LEVITON** company


APPLICATION

The Brand-Rex C6F/FTP D_{ca} cables are compliant with the European Construction Products Regulation, achieving Euroclass level D_{ca} according to EN 13501-6. These D_{ca} Euroclass cables also have superior levels of smoke emission, flaming droplets and acid gas production making them a versatile choice for many internal installations. The C6F/FTP D_{ca} Euroclass cables are suited to many high density backbone installations where people safety in the case of fire is a high priority.

The Brand-Rex C6F/FTP cables exceed the Category E performance standards. They are rated to 250MHz and are suitable for use in all Class E structured wiring cable systems. The applications supported include Gigabit Ethernet, PoE, PoE+ and broadband video transmissions at frequencies as high as 250MHz.

FEATURES AND BENEFITS

- 23 AWG Solid Annealed Copper Wire
- 4 Twisted Pairs Individually Screened and cabled together – providing EMI immunity
- Overall Aluminium Polyester Screen – for improved shielding efficiency and increased heat dissipation
- Designed to Support all Class E protocols including Gigabit Ethernet
- Supports Power Over Ethernet (PoE) and Power Over Ethernet Plus (PoE+) Applications
- HFFR-LS* material meets the requirements of the Construction Products Regulation (CPR) Euroclass D_{ca}
- Blue† Coloured Jacket to identify Euroclassification level D_{ca}
- Included in the Leviton and Brand-Rex 25 Year System Warranties when used in conjunction with Leviton or Brand-Rex copper connectivity. System warranties available for qualified projects installed by certified contractors



* Halogen Free Flame Retardant – Low Smoke

† Also available in a range of non-standard colours

STANDARDS

Applicable Cable Standards: IEC 61156-5 and EN50288-5-1

REACTION TO FIRE

CHARACTERISTIC	STANDARD	RATING
Single Cable Flame Rating	IEC 60332-1-2	Pass
Bundled Cable Flame Rating	EN 50399 20.5kW source	D _{ca}
Smoke Production	EN 50399	s1
Flaming Droplets / Particles	EN 50399	d2
Acid Gas Emission / Acidity	EN 50267-2-3	a1
Euroclassification	EN 13501-6	D _{ca} s1 d2 a1

Category 6 F/FTP Euroclass D_{ca} Cables

Datasheet: GD103610v1



PRIMARY ELECTRICAL PARAMETERS

CHARACTERISTIC	SPECIFICATION	TYPICAL PERFORMANCE @ 20°C
Conductor Loop Resistance	Max 19 Ω / 100m	14Ω / 100m
Conductor Resistance Unbalance	Max 2%	0.1%
Insulation Resistance	>5GΩ.km	>50GΩ.km
Dielectric Strength	2500 Vdc/2secs	Pass

SECONDARY ELECTRICAL PARAMETERS

CHARACTERISTIC	SPECIFICATION	TYPICAL PERFORMANCE @ 20°C
Velocity of Propagation	<534nsec/100m @ 100MHz	413nsec/100m @ 100MHz
Delay Skew	Max 45nsec/100m @ 100MHz	4nsec/100m @ 100MHz
Mean Characteristic Impedance	100Ω +/- 5Ω @ 100MHz	100Ω ± 3Ω @ 100MHz
Coupling Attenuation	Type 1b	84dB
Transfer Impedance	Grade 2	11mΩ/m @ 10MHz

ELECTRICAL PERFORMANCE

Frequency (MHz)		1	4	10	20	100	200	250	500	550
Insertion Loss (dB/100m)	Standard	2.1	3.8	6.0	8.5	19.9	29.1	33.0	na	na
	Typical	1.9	3.5	5.5	7.8	18.0	26.1	29.4	43.0	45.4
NEXT (dB)	Standard	66.0	65.3	59.3	54.8	44.3	39.8	38.3	na	na
	Typical	100.0	100.0	100.0	100.0	94.3	88.9	87.1	81.7	81.0
PSNEXT (dB)	Standard	64.0	63.3	57.3	52.8	42.3	37.8	36.3	na	na
	Typical	97.0	97.0	97.0	97.0	91.3	85.9	84.1	78.7	78.0
ELFEXT (dB/100m)	Standard	66.0	58.0	50.0	44.0	30.0	24.0	22.0	na	na
	Typical	90.0	90.0	90.0	84.8	70.8	64.8	62.8	56.8	56.0
PSELFEXT (dB/100m)	Standard	64.0	55.0	47.0	41.0	27.0	21.0	19.0	na	na
	Typical	87.0	87.0	87.0	81.8	67.8	61.8	59.8	53.8	53.0
Return loss (dB)	Standard	na	23.0	25.0	25.0	20.1	18.0	17.3	na	na
	Typical	27.0	30.0	30.0	30.0	25.1	23.0	22.3	20.2	19.9
ACR (dB/100m)	Typical	98.1	96.5	94.5	92.2	76.3	62.8	57.7	38.7	35.6
PSACR (dB/100m)	Typical	95.1	93.5	91.5	89.2	73.3	59.8	54.7	35.7	32.6

Category 6 F/FTP Euroclass D_{ca} Cables

Datasheet: GD103610v1

Brand-Rex a LEVITON company

INSTALLATION

Temperature (Installation)	0°C to +50°C	Min Bend Radius (Installation)	8 x Outer Diameter
Temperature (Operation)	-20°C to +75°C	Min Bend Radius (Operation)	4 x Outer Diameter
Max Tensile Load (Installation)	10kg per simplex cable	Field Test NVP Value	0.80
Segregation Class	Class D		

PRINT LEGEND

Example print legend:

[Length Mark]m BRAND-REX a LEVITON company C6F/FTP-Dca Cat 6 F/FTP EN 50399 Euroclass Dca s1 d2 a1 NVP 0.80 MADE IN UK [ID number] [Week/Year]

STANDARD PACKAGING SPECIFICATIONS

Brand-Rex Part Number	Packaging Length (m)	Colour	Nominal Cable Diameter (mm)	Nominal Cable Weight (kg/km)	Reel Size Flange x Width (mm)	Gross Weight (kg/Item)	Items Per Pallet
C6F/FTP-Dca-500BU	500	Blue†	7.1	50.4	465 x 390	27.7	12
C6F/FTP-Dca-1000BU	1000	Blue†	7.1	50.4	600 x 325	56.4	6

†Also available in a range of non-standard colours

“Brand-Rex is dedicated to designing, developing and manufacturing sustainable high performance structured cabling and speciality cabling solutions”

The information contained in this document is valid and correct at the time of issue. Brand-Rex reserves the right to modify details without notice in light of subsequent standard/specification changes and ongoing technical developments.