

## Features

- Manufactured in zero halogen DuPont Zytel 6.6 material.
- Cable ties can be installed by hand or by using one of our tensioning tools.
- High resistance to: brake fluids, lubricants, power steering fluids, oil, grease, paints, lacquers, detergents, animal and vegetable fats, gasoline and alkalis up to 40%
- Do not store or use in direct sunlight. (except for UV resistant ties)
- Store in the original packaging, Use as soon as possible after opening.
- Although Nylon cable ties have a wide operating temperature range it is not recommended that they be stored or installed at extremes of temperature.
- Supplied in pack of 100
- Available in black or natural.



## Technical Information

Operating Temperature range	-40°C to +85°C
Flame Resistance	UL94 V2 self extinguishing, zero halogen.
Recommended Storage temp	+15°C to +30°C at 50% humidity.

## Product Codes

PART CODE	LENGTH(MM)	WIDTH(MM)	MAX BUNDLE DIA(MM)	MIN. TENSILE STRENGTH(KG)	COLOURS
CT25100B	100	2.5	15	8	Black/Natural
CT36140B	140	3.6	33	18	Black/Natural
CT48160B	160	4.8	38	22	Black/Natural
CT48200B	200	4.8	50	22	Black/Natural
CT48300B	300	4.8	76	22	Black/Natural
CT48430B	430	4.8	110	22	Black/Natural
CT76150B	150	7.6	36	55	Black/Natural
CT76300B	300	7.6	76	55	Black/Natural
CT90530B	530	9.0	140	75	Black/Natural

\*Change "B" to "N" for Natural colour ties