

TP-CP-KF-LG-25PK

(25 PACK) TRUPORTAL CREDENTIAL - SLENDER - TRUPORTAL LOGO- PROXIMITY (EM)



Details

- Read only for CSN

TP-CP-KF-LG-25PK

(25 PACK) TRUPORTAL CREDENTIAL - SLENDER - TRUPORTAL LOGO- PROXIMITY (EM)

Technical Specifications

Technology

Credential Type	Proximity
Credential Operating Frequency	125 KHz
Support Technology 125 KHz	GE ProxLite/CASI Prox

System

Reading Distance	5 to 10 cm
Custom Data Model	No
Card Slot Punch	No

Printing

Direct Surface Printing	No
Thermal Transfer Printing	No

Ordering information

Minimum Order Quantity	1
Cards/tags in package	25
Special Card Order Form Required	No

Physical

Surface Cover	Glossy
Material	PVC
Form factor	KeyFob
Physical dimensions	105 x 115 x 32 mm
Net weight	270 g
Shipping weight	277 g
Colour	Orange

Environmental

Operating temperature	-10 to 45°C
Storage temperature	-10 to 45°C
Relative humidity	5 to 95% noncondensing

Standards & regulation

Compliancy	RoHS
------------	------

Dimensions

110 mm x 20 mm x 3 mm

Material

PVC

Frequency

125 KHz

Reading distance

0-10 cm

For use on

T100A & T100B

Color

Orange

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.